

## PC42d

### 4" Direct Thermal Desktop Printer

Featuring a solid double-layer housing, easy paper-loading design and media auto-centering function, the compact and elegant PC42d printer is easy to operate. Powerful and reliable, the PC42d printer is well suited for a variety of low-to-mid intensity thermal printing applications – such as electronic express and logistics waybills, healthcare laboratory labels and wristbands, retail price tags and receipts, distribution center routing labels, boarding passes and the like.

With 128 MB Flash and 64 MB SDRAM, which is several times larger than its competitors and supports up to a 32 GB USB expansion, the PC42d printer provides strong tag data pre-processing and caching capabilities. With an ARM926 core and 400 MHz high-speed processor, it can process high-volume tasks efficiently.

The PC42d printer delivers flexible industry-standard connectivity, with up to four built-in interface options: standard USB device and USB host, plus serial or Ethernet. With the rich interfaces, the PC42d printer easily integrates into virtually any application environment. The PC42d printer supports ZPL-II and EPL emulation, along with Direct Protocol (DP), and auto-senses the printing languages without any pre-setting, providing an easy upgrade path for competitive printers.

With a high-quality print head, advanced thermal management algorithms and broad thermal media compatibility, the PC42d printer delivers excellent printing results in an affordable, dependable desktop printer.



*A powerful and reliable desktop printer, the PC42d printer is well suited for a variety of low-to-mid intensity thermal printing applications.*

## FEATURES & BENEFITS



Compact yet powerful – a perfect combination of economy and quality.



Easy to use with a solid double-layer housing, simple paper-loading design, media auto-centering and auto-sensing of printing languages.



A high-quality print head and compatibility with a wide range of thermal media ensures excellent printing results.



Includes integrated command languages: ESim (EPL), ZSim (ZPL-II) and Direct Protocol (DP) with preset Chinese fonts.

# PC42d Technical Specifications

## PHYSICAL CHARACTERISTICS

**L x W x D:** 222.5 mm x 184 mm x 174 mm  
(8.8 in x 7.3 in x 6.9 in)

**Weight:** 1.5 kg (3.3 lb)

## MEDIA

**Max. Media Diameter:** 127 mm (5 in)

**Media Core Size:** 25.4 mm (1 in), 38.1 mm (1.5 in)

**Media Width:** 25.4 mm – 110 mm (1 in – 4.33 in)

**Label Length:** 9.6 mm – 99 cm (0.34 in – 39 in)

## PRINT TECHNOLOGY

**Printer Type:** Direct Thermal

**Print Resolution:** 8 dpmm (203 dpi)

**Max. Print Speed:** 100 mm/s (4 ips)

**Max. Print Width:** 104 mm (4.1 in)

## MEMORY

**Standard:** 128 MB Flash, 64 MB SDRAM

**Optional:** Up to 32 GB (via user-supplied USB thumb drive) formatted as FAT16 or FAT32

## COMMUNICATIONS

**Standard Interfaces:** USB Device, USB Host

**Built-in Options:** Ethernet (NIC), Serial

**Protocols/Network:** TCP/IP-suite (TCP, UDP, ICMP, IGMP), DHCP, BOOTP LPR FTP web page and Telnet 9100 IPv4

**Protocol/Serial Flow Control:** XON/XOFF RTS/CTS

## USER INTERFACE

**Display:** One feed button and LED display

**Web Page Languages:** English and Simplified Chinese (Default), Spanish, Portuguese, Russian, Korean

## GRAPHICS AND BARCODES

**Native Graphic Formats:** 1-bit BMP GIF PCX PNG

**Barcode Symbolologies:** All standard 1D and 2D symbolologies, including Aztec, Code 16K, Code 49, Data Matrix, DotCode, EAN-8, EAN-13, EAN.UCC 128, Grid Matrix, HIBC 39, HIBC 128, MaxiCode, MSI (modified Plessey), PDF417, Micro PDF417, Planet, Plessey, Postnet, QR-Code, RSS-14 (variations), Hanxin Code

## SOFTWARE

**Printer Command Languages:** Auto-Sense, Direct Protocol (DP), ZSim II (ZPL), ESim (EPL)

**Drivers:** InterDriver™ Windows Printer Driver

**Applications:** BarTender™ Ultralite

**Device Management:** Simple Diagnostic Tool

**Character Sets:** English & Extended Latin, Arabic, Baltic & Baltic Rim, Cyrillic, Greek, Hebrew, Thai, Turkish, Vietnamese and other Monotype™ Universal Font Scaling Technology (UFST) and WorldType Layout Engine (WTLE)

**Resident Fonts:** Monotype UFST+WTLE Andale Mono, Andale Mono Bold, OCR-A, OCR-B, Univers, Univers Bold, Univers Condensed Bold, CG Triumvirate Condensed Bold, MHeiGB18030C\_Medium (Simplified Chinese GB18030)

**Other Fonts – Downloadable:** MSung HK Medium (scalable TTF fonts), other required TTF fonts

## ENVIRONMENTAL

**Operating Temperature:** +5°C to +40°C (+41°F to +104°F) 15% to 80% RH, non-condensing

**Storage Temperature:** -40°C to +60°C (-40°F to +140°F) @ 10% to 90% RH

**Noise Level:** <70 dB

## ELECTRICAL

**Input:** 100–240V AC @ 50–60 Hz 1.5 A

**Output:** 24V DC 2.5 A

## OPTIONS AND UPGRADES

**Factory-Installable:** Ethernet, Serial

## APPROVALS

**Regulatory:** CCC, CB, CE, EMC, cULus, FCC, CRS, EAC, NOM

**Europe:** D Mark, EN 60950-1; CE Europe EMC Directive (EN55022 Class A + EN55024)

## WARRANTY

One-year standard warranty

## For more information

[www.honeywellaidc.com](http://www.honeywellaidc.com)

## Honeywell Safety and Productivity Solutions

9680 Old Bailes Road

Fort Mill, SC 29707

800-537-6945

[www.honeywell.com](http://www.honeywell.com)